

04676.P008X

Patent

UNITED STATES PATENT APPLICATION

for

DISTINCTIVE VIBRATE SYSTEM,  
APPARATUS AND METHOD

INVENTOR:

**Joe Freeman Britt, Jr.**

Prepared by:

BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN, LLP  
12400 WILSHIRE BOULEVARD  
SEVENTH FLOOR  
LOS ANGELES, CALIFORNIA 90025  
(408) 720-8598

Attorney's Docket No. 04676.P008X


"Express Mail" mailing label number EL143567808US

Date of Deposit March 9, 2001

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. 1.10 on the date indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

Leah Resendez

(typed or printed name of person mailing paper or fee)



(Signature of person mailing paper or fee)

# DISTINCTIVE VIBRATE SYSTEM, APPARATUS AND METHOD

## BACKGROUND OF THE INVENTION

### Field of the Invention

5           This invention relates generally to the field of network data services. More particularly, the invention relates to an apparatus and method for managing network portal data.

### Description of the Related Art

10           “Portals” are World Wide Web (“WWW”) sites which help users manage and navigate through vast amounts of information stored on the Internet. Some well known Internet portals include “Yahoo!®,” AltaVista®, and Excite®. Portals typically provide search features which allow users to search for particular types of content by entering keywords. In response to the keyword search request, the portal returns links to relevant Internet sites and/or relevant  
15           content stored directly on the portal. For example, if a user enters the keyword “snowboarding,” the portal may return a list of hyperlinks to Internet sites related to snowboarding as well as internal portal categories related to snowboarding (e.g., “Recreation > Sports > Snowboarding”).

20           In addition to the keyword search and content management capabilities described above, portals may also provide users with a variety of network applications such as, for example, email, electronic scheduling and contact

management, chat groups, newsgroups, personal financing, and instant messaging, to name just a few.

Many portals also provide a registration feature which allows users to customize the types of information and/or applications which will be immediately accessible to the user on the portal. For example, the user may configure the portal to automatically retrieve and display information specified by the user such as, for example, the value of the user's stock portfolio, the weather forecast in the user's geographic location, an indication of any unread email messages, the user's appointments for the day, the local news headlines for the day, and/or the television listings for the user's favorite channels that evening.

When the user visits the portal (e.g., via a client computer), he/she may be presented with a single Web page that contains all of the foregoing information, automatically collected and transmitted by the portal. Typically, a portal will transmit a unique Web page and associated data to the user in this manner only after receiving proper authentication (e.g., user ID and password).

## SUMMARY

An apparatus is disclosed which is configured to announce a transmission from a caller by vibrating in a predetermined manner associated with the caller.

Also disclosed is a method comprising: receiving a transmission from a first  
5 caller; identifying the first caller; and vibrating a device in a predetermined manner based on said first caller's identity.

10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
2218  
2219  
2220  
2221  
2

## BRIEF DESCRIPTION OF THE DRAWINGS

A better understanding of the present invention can be obtained from the following detailed description in conjunction with the following drawings, in which:

5           **FIG. 1** illustrates an exemplary network architecture used to implement elements of the present invention.

**FIG. 2** illustrates another exemplary network architecture used to implement elements of the present invention.

10           **FIG. 3** illustrates a radio signal including its sub-carrier in the frequency domain.

**FIG. 4** illustrates an external view of a portal device according to one embodiment of the invention.

**FIG. 5** illustrates an internal view of a portal device according to one embodiment of the invention.

15           **FIG. 6** illustrates a process according to one embodiment of the invention wherein a user is logged in to a portal server.

**FIG. 7** illustrates a visual programming interface according to one embodiment of the invention.

20           **FIG. 8** illustrates portal device communication according to one embodiment of the invention.

**FIG. 9** illustrates one embodiment of a portal device communicating with a portal server.

**FIG. 10** illustrates one embodiment of the invention which employs a distinctive vibrate feature.

FIG. 9 illustrates one embodiment of a portal device communicating with a portal server.

## DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the present invention. It will be apparent, however, to one skilled in the art that the present invention may be practiced without some of these specific details. In other instances, well-known structures and devices are shown in block diagram form to avoid obscuring the underlying principles of the present invention.

### AN EXEMPLARY NETWORK ARCHITECTURE

Elements of the present invention may be included within a client-server based architecture 100 such as that illustrated in **Figure 1**. According to the embodiment depicted in **Figure 1**, a portal server 110 communicates with clients 140 and other network servers 130 over a network 120 (e.g., the Internet). The network 120 over which the clients 140 and servers 110, 130 transmit and receive data may be comprised of any combination of private (e.g., leased) and/or public communication channels. These may include, for example, Digital Signal ("DS") channels (e.g., DS-3/T-3, DS-1/T1), Synchronous Optical Network ("SONET") channels (e.g., OC-3/STS-3), Integrated Services Digital Network ("ISDN") channels, Digital Subscriber Line ("DSL") channels, cable modem channels and a variety of wireless communication channels including satellite broadcast and cellular channels.

In addition, various networking protocols may be used to support communication across the network 120 including, for example, the Asynchronous Transfer Mode ("ATM"), Ethernet, and Token Ring (at the data-link level); as well as Transmission Control Protocol/Internet Protocol ("TCP/IP"), Internetwork Packet Exchange ("IPX"), AppleTalk and DECnet (at 5 the network/transport level). It should be noted, however, that the principles of the invention are not limited to any particular communication channel or protocol.

The portal server 110 in one embodiment includes a user database for 10 storing various types of user configuration and account data. Users may register and login to the portal server 110 from a client 140 by specifying a user ID and/or password. According to one embodiment, a user connects to the servers 110, 130 via a browser application such as Netscape Navigator™ or Microsoft Internet Explorer™ which communicates via the Hypertext Transfer Protocol 15 (hereinafter "HTTP").

In one embodiment, users may configure the portal server 110 to retrieve and manage specific types of information. For example, a user may configure the portal server 110 to retrieve up-to-date stock quotes for a specified set of stocks (e.g., reflecting the user's portfolio), to collect the weather forecast for the user's 20 hometown, and/or to retrieve recent articles relating to a particular sports



franchise. The portal server will then retrieve the specified information from other servers (e.g., server 130) on behalf of the user.

In addition to information retrieval and management, in one embodiment the portal server 110 also provides application services such as email, online  
5 scheduling (e.g., appointments, to-do lists, etc), instant messaging, contact management, word processing and a variety of other online services. Users may access these services by logging in to the portal server 110 with a valid user ID and password. In one embodiment, the portal server 110 generates a unique, personalized Web page for each user containing links to all, or a subset of, the  
10 information and/or services subscribed to by the user.

## EMBODIMENTS OF THE INVENTION

In one embodiment, a portal device 150 stores and processes user-specified information and/or programs as well as non-user-specified information/programs (e.g., targeted advertisements based on the user's profile).  
15 The information/programs may be transmitted to the portal device 150 through the client 140, and/or directly via wireless broadcast (as illustrated in **Figure 2** and described in detail below). Thus, the portal device 150 in this embodiment is a removable extension of the portal server 110, storing a subset of the information and services maintained by the portal server 110 on behalf of the  
20 user. For example, a user may configure the portal server 110 to periodically download the user's to-do list (or other scheduling data) to the portal device

(e.g., every morning, every two hours, every time the user connects the portal device to the client 140, etc). When the user leaves the office, he/she can simply take the portal device with him/her and view his/her schedule throughout the day.

5           The timing of the information/program download may depend on the particular embodiment of the portal device 150. For example, if a wireless embodiment is used (described below) downloads may occur at any time when the portal device 150 is within wireless transmission range, whereas if a non-wireless embodiment is used, downloads may be limited to periods of time when  
10   the portal device 150 is connected to the portal server 110.

          In one embodiment, the user may customize the portal device 150 preferences and content which will be downloaded to the portal device 150 from the portal server 110. This may be accomplished, for example, by selecting certain preferences/content from a portal server 110 Web page (e.g., by using an  
15   online programming interface as described below). For example, the user may choose to have each day's to-do list downloaded to his portal device 150 and may also program the device 150 (e.g., via the portal server 110) to continually display the next scheduled event for the day. Various other user interface and content-based data may be transmitted to the portal device 150 from the portal  
20   server 110 while still complying with the underlying principles of the invention.

### *Client Link*

As illustrated in **Figure 1**, one embodiment of the portal device 150 communicates to the portal server 110 via a communication link 160 with the client 140. The communication link may be established via a physical I/O connection with the client 140 such as a Universal Serial Bus ("USB") interface or a communication ("serial") interface. Alternatively, the communication link 160 may be a wireless link such as an Infrared I/O channel or a radio frequency ("RF") I/O channel.

In one particular embodiment, the client link 160 is formed using a capacitively-coupled communication channel. As is known in the art, a capacitor is any dielectric sandwiched between two conductive elements. In this embodiment, one of the two conductive elements is located within the portal device 150 and the second of the two conductive elements is located external to the portal device 150 and is communicatively coupled to an I/O port of the client 140. For example, in one embodiment, the second conductive element may be disposed within user's mouse pad. According to this embodiment, the user may simply place the portal device on the mouse pad to set up the capacitive communication link 160 with the client 140. It should be noted, however, that various other client links 160 may be employed while still complying with the underlying principles of the invention.

### *Direct Radio Broadcast*

In one embodiment, illustrated in **Figure 2**, data and/or programs are transmitted to the portal device 150 from the portal server 110 over an RF link 220. In this embodiment, the organization maintaining the portal server 110 and/or implementing other features of the system and method described herein (hereinafter the “portal organization” or “PO”), may lease a portion of the RF transmission bandwidth from one or more radio stations 210. It should be noted, however, that various RF transmission techniques may be used without departing from the underlying principles of the invention.

Referring to **Figure 3**, in one particular embodiment, the PO will use the radio station’s sub-carrier frequency band 320 to transmit data and/or programs to the portal device 150. As it is known in the art, radio stations are licensed a sub-carrier frequency block 320 along with the audio carrier frequency block 310. Although some radio stations use the sub-carrier frequency block 320 (e.g., for foreign-language broadcast), most do not. As such, the present embodiment provides a mechanism for transmitting data over an infrequently-used wireless transmission channel.

To further conserve bandwidth within the sub-carrier frequency block 320, in one embodiment, the data transmitted over the RF link 220 is not addressed to any one specific portal device. Rather, in this embodiment, the data is simply transmitted (e.g., with a tag that identifies the data) and is sensed by any portal

device(s) 150 listening within the sub-carrier block 320. This type of addressing will be referred to herein as "data addressable" addressing (in contrast to "device addressable" addressing in which a device address is associated with the transmitted data). The individual portal devices 150 that sense the various data transmissions may ignore them or may take some other specified action (e.g., store and display the transmitted data), depending on how the devices 150 are configured. For example, a portal device 150 may be configured by a user to track stock quotes for stocks within his/her portfolio and to ignore all other stock quotes. Similarly, the user may configure the portal device 150 to listen for local weather reports, local news headlines, and/or any other information which may be accessed by the user directly at the portal server 110.

In one embodiment, the data broadcast in a particular geographical region will be selected based on the number of users in that region who have registered on the portal server 110 and/or the types of data requested by users in the region. For example, if no users in the region have configured the portal server 110 to gather a particular stock quote, then the portal server 110 will not transmit that stock quote over the RF link 220 in that region. Similarly, the portal server 110 may be configured to only transmit local data such as weather and local news in the local broadcast region to which the weather and news pertains (i.e., where it will most likely be requested). Broadcasting data selectively in this manner will further improve bandwidth over the RF link 220 (i.e., by reducing unnecessary data transmissions).

In one embodiment, portal devices 150 may be addressed directly (e.g., by including the device's serial number or other ID code in an address field of the data transmission). This embodiment may be provided by the PO to users as a "premium" service, under which the user pays an additional fee to receive personally-addressed information over the sub-carrier 360 (e.g., email messages, daily schedules, etc), as well as the more general information described above. Users of this embodiment may be charged on a subscription basis and/or on a per-use basis, depending on the embodiment. Of course, other pricing models may be employed while still complying with the underlying concept. The PO may also employ this embodiment under certain emergency situations (e.g., where it is crucial that a particular user receive a data transmission immediately).

### *Embodiments of the Portal Device*

**Figure 4** illustrates an external view of one embodiment of a portal device 420 which may be used as a key chain. As shown, this embodiment includes a key chain ring 410 for securing a set of keys (or other personal effects) to the device 420. Also illustrated is a display 430 for displaying various types of portal data. In one embodiment the display is a Liquid Crystal Display ("LCD"). Of course, other display technologies may be implemented while still complying with the underlying principles of the invention (e.g., Light Emitting Diode ("LED") displays). Also included is a set of control buttons 440 and 441 for selecting menu items and/or jumping back and forth between stored portal data and a control knob 450 for scrolling between menu items and/or data. In one

embodiment, the control knob 450 rotates on an axis which is substantially perpendicular to the plane of the display 430.

Additional attachable embodiments of the portal device 150 include a necklace configuration, a pocket watch configuration, and a sports configuration (e.g., wherein the portal device is strapped firmly around a user's arm). In the latter configuration, the shell of the portal device may be comprised of a water-proof material to avoid water damage to the internal components of the device.

As illustrated in **Figure 5**, one embodiment of the portal device 150 is comprised generally of a microcontroller 505, an external memory 550, a display controller 575, and a battery 560. The external memory 550 may be used to store programs and/or portal data 565 transmitted to the portal device 150 from the portal server 110 (e.g., via client 140 and/or radio station 210). In one embodiment, the external memory 550 is non-volatile memory (e.g., an electrically erasable programmable read only memory ("EEPROM"); a programmable read only memory ("PROM"), etc). Alternatively, the memory 550 may be a volatile memory (e.g., random access memory or "RAM") but the data stored therein may be continually maintained via the battery 560. The battery 560 in one embodiment is a coin cell battery (e.g., of the same type used in portable electronic devices such as calculators and watches). In one embodiment, when the battery power decreases below a threshold level, the portal device 150 will notify the user and/or the portal server 110. The portal

server 110 in one embodiment will then automatically send the user a new battery.

The microcontroller 505 of one embodiment is comprised of a central processing unit ("CPU") 510, a read only memory ("ROM") 570, and a scratchpad RAM 540. The ROM 570 is further comprised of an interpreter module 520 and a toolbox module 530.

The toolbox module 530 of the ROM 570 contains a set of toolbox routines for processing data, text and graphics on the portal device 150. These routines include drawing text and graphics on the portal device's display 430, decompressing data transmitted from the portal server 110, reproducing audio on the portal device 150, and performing various input/output and communication functions (e.g., transmitting/receiving data over the client link 160 and/or the RF link 220). A variety of additional portal device functions may be included within the toolbox 530 while still complying with the underlying principles of the invention.

In one embodiment, microprograms and portal data 560 are transmitted from the portal server 110 to the external memory 550 of the portal device via a communication interface 570 under control of the CPU 510. Various communication interfaces 570 may be employed without departing from the underlying principles of the invention including, for example, a Universal Serial



Bus ("USB") interface or a serial communication ("serial") interface. The microprograms in one embodiment are comprised of compact, interpreted instructions known as "bytecodes," which are converted into native code by the interpreter module 520 before being executed by the CPU 510. One of the

5 benefits of this configuration is that when the microcontroller/CPU portion of the portal device 150 is upgraded (e.g., to a faster and/or less expensive model), only the interpreter module 520 and toolbox 530 of the ROM needs to be rewritten to interpret the currently existing bytecodes for the new

10 microcontroller/CPU. In addition, this configuration allows portal devices 150 with different CPUs to coexist and execute the same microprograms. Moreover, programming frequently-used routines in the ROM toolbox module 530 reduces the size of microprograms stored in the external memory 550, thereby conserving memory and bandwidth over the client link 160 and/or the RF link 220. In one embodiment, new interpreter modules 520 and/or toolbox routines 530 may be

15 developed to execute the same microprograms on cellular phones, personal information managers ("PIMs"), or any other device with a CPU and memory.

One embodiment of the ROM 570 may be comprised of interpreted code as well as native code written specifically for the microcontroller CPU 505. More particularly, some toolbox routines may be written as interpreted code (as

20 indicated by the arrow between the toolbox 530 and the interpreter module 520) to conserve memory and bandwidth for the same reasons described above with respect to microprograms. Moreover, in one embodiment, data and

microprograms stored in external memory 550 may be configured to override older versions of data/microprograms stored in the ROM 570 (e.g., in the ROM toolbox 530).

### *Data Compression*

5 As described above, microprograms and portal data may be transmitted to the portal device 150 in a compressed format. As such, in one embodiment, decompression logic is programmed into the microcontroller ROM 570 (e.g., within the toolbox 530) and is used to interpret and/or decompress the microprograms/data as they are received.

10 In one embodiment, a plurality of uncompressed data is stored in the ROM 570, and codes identifying the uncompressed data are transmitted across the RF link 220 and/or client link 160. For example, instead of transmitting the entire market code for a particular stock, such as "MSFT" for Microsoft, a compressed code, e.g., "M," may be transmitted to the portal device 150 instead.

15 The ROM 570 in this embodiment may include a lookup table (or similar decode logic) for retrieving the real market code "MSFT," using the compressed code, "M." Once the real code is retrieved from the ROM 570, it may be displayed on the portal device 150 as illustrated in **Figure 4**. It should be noted, however, that the underlying principles of the invention may be practiced using a variety of  
20 coding schemes and/or digital compression techniques.

### *User Registration and Authentication*

One embodiment of the invention will now be described with reference to the flowchart of **Figure 6**. According to this embodiment, when a user initially connects to the portal server 110 (e.g., from client 140), the portal server 110 will determine whether a portal device plug-in is installed on the user's Web browser (at 615). As is known in the art, plug-ins are auxiliary programs added to Web browsers to provide them with new levels of functionality. One embodiment of the present invention uses a plug-in to coordinate communication between the portal server 110, the client 140, and the portal device 150. In addition, the plug-in may convert and/or compress "standard" portal programs/data (e.g., programs/data meant to be executed on the client 140) into microprograms/data that the portal device can properly interpret, as described herein. If the plug-in is not installed, the portal server 110 may automatically transmit and install it on the client 140 (at 625).

At 630, the portal server 110 (e.g., via the plug-in) determines whether the portal device is currently attached to the client 140. If the device 150 is attached then, in one embodiment, the portal server 110 will automatically log the user in. The portal server 110 may automatically authenticate the portal device 150 via a serial number and/or a user authentication key embedded/stored in the device 150. Once the user is logged in to the portal server, he/she can then transmit data to and from the portal device 150 as described herein.

If the device 150 is not attached, however, then the portal server 110 may implement a standard user name/password login procedure and/or may register the user (at 640). During the registration process the user may be asked to respond to a series of questions relating to his/her background (e.g., hobbies, education, career, etc). The portal server 110 may use this information to personalize the content collected and provided to the user and/or to target ads to the user based on the user's preferences. In addition, at this point the user may be provided with an opportunity to configure the portal server 110 to gather and manage specific information on behalf of the user (e.g., particular stocks, sports scores, news, etc) and/or to provide the user with access to certain online applications (e.g., email, electronic scheduling, etc) as described herein.

### *Online Programming Interface*

In one embodiment, registered users are provided with an online visual programming interface such as that illustrated in **Figure 7**. Under this embodiment users may construct their own microprograms to be executed on the portal device 150 and/or the client 140. For example, a user may define a programming block as a hyperlink which points to a particular piece of data or series of data (e.g., a current stock quote for AT&T, the San Francisco weather forecast, etc) and may also indicate how frequently the data associated with the hyperlink is to be updated. Multiple such blocks may be chained together to create a continual sequence of information to be displayed on the portal device 150 or the client 140. The particular programs generated by users may depend

on whether a wireless portal device 150 is being used. For example, a microprogram designed to download up-to-date stock quotes may require a wireless connection to the portal server 110 to be effective.

As illustrated in **Figure 7**, users may also program animation and/or sound into the portal device 150. For example, block 710 points to a particular image file (e.g., a bitmap file) and block 715 points to a particular music file (e.g., a Musical Instrument Digital Interface or "MIDI" file). The user may cause the image to move across the display 430 of the portal device 150 in a specified direction by programming block 720 (e.g., using X and Y coordinate data). Concurrently, the user may program block 725 to play the music track identified in block 715. Temporal link 722 indicates that the movement of the image and the playback of the music track are to take place simultaneously. Programming block 720 indicates that the music and image will both fade out to end the program.

In one embodiment, standard image and/or music files stored on the client 140 are converted to a format which the portal device can interpret (e.g., using a conversion module which may included in the client plug-in). For example, the melody line may be extracted from a MIDI file and transmitted to the portal device as a series of notes. Similarly, bitmap or JPEG images may be converted so that they are properly displayed on the portal device display 430, which in one embodiment is a black & white LCD display.

### *Portal Key Operations*

In one embodiment, each portal device 150 includes a portal key which uniquely identifies the device, the user and/or particular data on the portal server. The key may either be permanently embedded in the device (e.g., the key may be the serial number) or, alternatively, may be selected manually by the user (e.g., the user's ID on the portal server 110) or may be assigned to the device by the portal server 110.

Regardless of how the portal key is generated, as illustrated in **Figure 8**, in one embodiment users may exchange keys between portal devices. Specifically, portal device 810 is shown receiving a portal key (key no. 5331998TW) from portal device 820. In one embodiment, when the user of portal device 810 connects to the portal server 110 after receiving the portal key, he/she will be provided with access to information and/or services associated with the portal key. For example, the user of portal key 820 may store personal and/or business-related information on the portal server 110 which he/she wants to share with the user of portal device 810.

Several portal key applications may be implemented using this type of portal key exchange. These include, for example, social invitations; "business card" exchanges (i.e., where the user of portal device 820 stores an online business card on portal server 110); personal photo exchanges; and/or exchanges of any other information adapted to be stored on a computer network. It should

be noted, however, that the underlying principles of the invention are not limited to any particular type of informational exchange.

Exchanging portal keys in the foregoing manner provides an efficient mechanism for exchanging information using a limited amount of portal device memory because the underlying information is stored on the portal server 110, rather than the portal device 150 itself. In addition, when a user exchanges a key, the user is then free to continually update the information/services on the portal server 110 to which the key provides access. For example, a user may exchange a key with a prospective employer, and subsequently update his/her resume on the portal server 110. Similarly, if the user is involved in research, he/she may exchange his/her key with colleagues and continually update the research data on the portal server 110.

In one embodiment, a user may set up a number of different keys on the portal server, each pointing to a different type of information and/or service.

The user can then select a particular key to transmit to a second user (e.g., using the portal device controls 440, 441, 450) depending on the information and/or service to be provided to the second user. For example, a user may establish a business key which points to business-oriented information/services (e.g., a firm brochure) and a personal key which points to personal information/services (e.g., personal photos). In one embodiment, the portal device 150 will include one standard key for generally identifying the portal device 150 to the portal

server 110 and other users, and any number of user-defined "sub-keys" which can be used to exchanged more specific user data (e.g., such as the business data and personal data described above).

Various advertising and promotional services may be implemented in accordance with the underlying principles of the invention. In one embodiment, portal devices may be set up to broadcast keys to users at a place of business such as a supermarket or a car dealership. A user may choose to receive the key on his/her portal device and thereby acquire additional information about the product/service associated with the key when he/she logs in to the portal server

110. Businesses may offer various types of Internet promotions/discounts to users in this manner. Conversely, a user may choose to transmit his/her key to a portal device located at a business to request that the business automatically contact the user with additional product/service information (e.g., via email, a telephone call, etc).

In one embodiment, advertisements and/or coupons may be transmitted to the user's portal device 150. This may be accomplished over the client link 160 and/or the RF link 220. If transmitted over the client link 160, the ad/coupon may be programmed to trigger at a statistically effective time (one embodiment of the portal device 150 includes a digital clock). For example, a Starbucks® Coffee ad may be downloaded to the portal device 150 at a random time and may be programmed to trigger in the morning, before the user heads in to work.



Personal information known about the user (e.g., the user's preferences, the user's daily schedule, etc) may be factored in to the timing decision and/or the decision as to which ads to transmit to the user. The ad/coupon may also be triggered automatically at any time/date via the RF link 220.

5           If a coupon is transmitted, the user may redeem the coupon in a number of ways. In one embodiment, the user may simply show the coupon code to an employee working at the business for which the coupon is valid. Alternatively, a portal device may be configured directly at the business to automatically redeem coupons (e.g., via a coupon exchange feature similar to the key exchange feature  
10       described above). The business' portal device may communicate with the portal server 110 to continually transmit and receive coupon data. In one embodiment, the user's portal device is configured to display a bar code identifying the received coupon/service which may be interpreted by a bar code device at the business to redeem the coupon/service. The underlying principles of the  
15       invention may be implemented using various additional advertisement and/or coupon redemption mechanisms.

          In one embodiment, a coupon or advertisement may be transmitted to the user's portal device 150 from a portal device located at a business (in contrast to the embodiment above, where the coupon/advertisement is transmitted by the  
20       portal server 110). In this embodiment, the user's portal device 150 may automatically trigger the advertisement/coupon when it is brought within range

of the business' portal device. In one embodiment, the business' portal device transmits a key to the user's portal device 150, which the user may subsequently use to obtain additional information from the portal server 110 (e.g., relating to a particular product or service). In this embodiment, the business' portal device  
5 may or may not communicate directly with the portal server 110.

It should be noted that the foregoing description of portal devices and associated methods includes various business methods. In addition, according to one particular business method, once a user registers on the portal server 110, the PO will assign a portal device 150 to the user free of charge (or for some nominal  
10 fee). Upon receipt of the portal device 150 (e.g., in the mail), the user will attach the portal device (e.g., via the client link 160), and register the portal device 150 with the portal server 110. The user may then configure the manner in which he/she will use the portal device 150 (e.g., by selecting the types of portal data/microprograms to be processed and stored in the device). In one  
15 embodiment, users will be given the option to upgrade to a more advanced portal device 150 for a specified fee. In one embodiment, however, the fee will be no more than the cost of manufacturing and shipping the device to the user.

In one embodiment, the portal device 150 is shipped to the user with pre-configured data and/or advertisements already stored within the device 150.

20 This may include, for example, the user's name and address; scheduling data for

the user for the day/week on which the user will receive the device; and/or any other data stored by the user on the portal server 110.

In one particular embodiment, the portal device 150 is configured to display shipping information (e.g., the shipping bar code and/or destination address) on its display 430. This shipping information may be used by the shipping company to transport the portal device 150 to the user. This embodiment may be shipped to the user using transparent packaging so that the shipping data may be easily read/scanned.

### *Additional Embodiments*

As mentioned above, the portal device 150 may communicate with the portal server 110 using various RF communication techniques. For example, in one particular embodiment, the portal device 150 transmits and receives data to/from a cellular network via the cellular digital packet data ("CDPD") standard. As it is known in the art, the CDPD standard is a digital wireless standard that is deployed as an enhancement to the existing analog cellular network. It provides a packet overlay onto the AMPS network and moves data at 19.2 Kbps over continuously-changing unused intervals in standard voice channels. Accordingly, this embodiment of the portal device is capable of exploiting normally unused bandwidth on a nation-wide, analog cellular network. Embodiments of the portal device may also be configured to transmit/receive data using a variety of other communication standards

including 2-way paging standards and third generation ("3G") wireless standards (e.g., UTMS, CDMA 2000, NTT DoCoMo, . . . etc).

As described above, because certain embodiments of the portal device 150 are configured to process hardware-independent interpreted code (e.g., via an interpreter module 520 such as a Java virtual machine), applications may be ported to new hardware platforms without significant changes. In addition, as illustrated in **Figure 9**, in one embodiment, communications functionality is provided via a modular networking interface 916, which may be easily modified/replaced without altering existing portal device applications 910 or significant portions of the bytecode interpreter 912. For example, when changing from a CDPD network to a 3G network, only the network interface component 916 of the VM interpreter 912 will need to be updated (along with any required 3G hardware 914) to support the new 3G protocol.

As described above (and as indicated in **Figure 9**), in one embodiment, the interpreter module 912 on the portal device 150 is a Java virtual machine. As such, this embodiment of the portal device 150 is capable of executing a vast library of existing hardware-independent Java applications (e.g., applets/bytecodes) 910. Moreover, as indicated in **Figure 9**, one embodiment of the portal device employs a 32-bit RISC-based microprocessor such as an ARM processor. As is known in the art, ARM processors are widely used in PDAs, cell phones and a variety of other wireless devices. It should be noted, however, that

various other hardware and software (and/or firmware) architectures may be used for the portal device 150 while still complying with the underlying principles of the invention.

As described above, one embodiment of the portal server 110 converts standard applications and data into a format which the portal device 150 can properly interpret. Accordingly, as illustrated in **Figure 9**, this embodiment of the portal server 110 may include a content conversion module 920 for processing portal device 150 requests for Internet content 940. More particularly, in one embodiment, the portal server 110 acts as a proxy for the portal device 150, forwarding Internet requests 940, 941 to the appropriate Internet site 130 on behalf of the portal device 150, receiving responses from the Internet site 130 in a standard Internet format (e.g., Web pages with embedded audio/video and graphical content), and converting the standard Internet responses 924 into a format which the portal device 150 can process (e.g., bytecodes).

For example, the conversion module 920 may include a hypertext markup language ("HTML") rendering module (not shown) for interpreting HTML code and downloading any embedded content in the HTML code (e.g., graphics, video, sound, . . . . etc) to the portal server 110. The conversion module 920 may then combine the HTML code and embedded content and generate a set of bytecodes for accurately reproducing the requested content on the portal device 150. As described above, in one embodiment, the bytecodes may be Java

bytecodes/applets. However, various other types of interpreted and/or non-interpreted code may be generated, depending on the particular type of portal device 150 being used (e.g., one with an interpreter module or one without).

Because the portal server 110 has an intimate knowledge of the capabilities/configuration of each portal device 150 (e.g., screen size, graphics/audio capabilities, available memory, processing power, user preferences, . . . etc) it can reconstruct the requested Internet content accurately, while at the same time minimizing the bandwidth required to transmit the content to the device 150. For example, the conversion module 920 may perform pre-scaling and color depth adjustments to the requested content so that it will be rendered properly within the portal device 150 display. In making these calculations, the conversion may factor in the memory and processing power available on the portal device 150. In addition, the conversion module 920 may compress the requested content using a variety of compression techniques (and thereby preserve network bandwidth).

In one embodiment, the conversion module 920 will simply discard Internet content which either cannot be reproduced on the portal device 150, or which the user has indicated that he/she does not want to be reproduced on the portal device. For example, a user may indicate that he/she does not want sounds to be generated on the portal device 150 or that he/she does not want advertisements transmitted to the portal device 150. The conversion module 920

will then remove any sounds or advertisements embedded in the requested Web page (or other requested Internet content). Because HTML rendering and other advanced processing of Internet content/data is offloaded to the portal server 110 as described above, the portal device 150 can be manufactured using a low power microprocessor or microcontroller, thereby lowering the cost of manufacture and/or the energy consumed by the device 150.

In one embodiment, when a particular Web page or other Internet object has been converted into a format suitable for execution on the portal device 150 (e.g., Java bytecodes and data) the formatted page/object may be stored locally on a cache 925 at the portal server 110 (or other server maintained by the PO). Thus, the next time the content is requested, the conversion module 920 may simply read the previously-generated code from the local cache 925 (i.e., it will no longer need to retrieve the content from remote locations to reconstruct the code).

Various caching techniques and algorithms may be implemented to ensure that the cache 925 is storing Internet data efficiently (i.e., resulting in an acceptable percentage of cache 'hits') and that the data is current. For example, the portal server 110 may cache the most frequently-requested Internet data (e.g., the Yahoo™ home page), and may remove content from the cache based on a least-recently used caching policy. In addition, to ensure that data stored in the cache is current, the portal server 110 may compare the version of the data stored

in the cache 925 with the version of data stored at the remote Internet site 130 when the data is requested. Similarly, the portal server 110 may store data in the cache 925 for some predetermined period of time before checking the remote server 130 for a new version. Various other Internet caching techniques may be employed while still complying with the underlying principles of the invention (e.g., those defined in the Internet Caching Protocol ("ICP") and/or the Cache Array Routing Protocol ("CARP")).

### *Distinctive Ring and Distinctive Vibrate*

As is known in the art, many wireless and non-wireless telephony devices offer "distinctive ring" features. For example, using automatic number identification ("ANI," commonly known as caller ID) techniques, a telephony device may be configured to identify a caller and ring in a specified way based on the identity of the caller. For example, a user may configure his/her telephone to announce a call from "Caller A" by two short rings followed by a third long ring. Distinctive ring features are particularly useful for telephones which do not have caller ID displays and/or in situations where the caller ID displays are not easily viewable.

Many wireless and non-wireless telephony devices also include a "vibrate alert" feature which, when selected by the user, will cause the telephony device to vibrate rather than ring. This feature is particularly useful in situations where the user does not wish to disturb others with the ringing sound of his/her



telephony device (e.g., in a movie theater or a conference). However, when the “vibrate alert” feature is activated, current telephony devices do not provide users with the ability to identify the caller (i.e., without looking at the device’s display).

5 One embodiment of the invention, illustrated generally in **Figure 10**, includes a “distinctive vibrate” feature which allows users to identify callers based on the manner in which the portal device 150 vibrates. For example, according to this embodiment, if a user configured his/her portal device 150 to announce a call from “Caller A” by two short rings followed by a third long ring, 10 when that user switches the portal device to “distinctive vibrate” (e.g., during a meeting) a call from “Caller A” will then be announced by two short vibrate periods followed by one long vibrate period. It will be appreciated that various other ring/vibrate “fingerprints” may be configured consistent with the underlying principles of the invention.

15 In one embodiment, a list/table of callers and associated ring/vibrate fingerprints may be stored directly on the portal device 150. Alternatively, the list/table of callers and associated ring/vibration fingerprints may be stored directly on the portal server 110. The underlying principles of the invention remain the same regardless of how/where the distinctive ring/vibrate list is 20 stored.

In one embodiment, the portal device 150 (or other device) may be configured to vibrate/ring a particular way to announce a particular “caller” regardless of the medium through which the “call” is transmitted. For example, returning to the example above, the user of the portal device 150 may configure the device (in conjunction with the portal sever 110) to vibrate/ring in the same manner for emails, IP telephony calls, instant messages, etc, transmitted by Caller A (i.e., in addition to standard telephone calls). Alternatively, or on addition, the portal device 150 may be configured to vibrate/ring in a slightly different manner when Caller A transmits an email message than when Caller A makes a telephone call. For example, the vibration/ring pattern may be the same but it may be followed by an additional vibration/ring. Alternatively, or in addition, the speed of the vibration/ring pattern may be different. Various other vibration/ring patterns may be employed to identify “callers” consistent with the underlying principles of the invention.

In one particular embodiment, the frequency of the portal device’s 150’s vibration may be configured to identify the caller and/or transmission medium. For example, 60 Hz may identify Caller A, 120 Hz may identify Caller B and 180 Hz may identify Caller C. The frequency may be used to identify callers alone or in combination with the patterned vibrations described above (e.g., two short rings/vibrations followed by a third long ring/vibration at 60 Hz identifies Caller A whereas two short rings followed by a third long ring at 180 Hz identifies Caller B).

Embodiments of the invention may include various steps as set forth above. The steps may be embodied in machine-executable instructions. The instructions can be used to cause a general-purpose or special-purpose processor to perform certain steps. Alternatively, these steps may be performed by specific hardware components that contain hardwired logic for performing the steps, or by any combination of programmed computer components and custom hardware components.

Elements of the present invention may also be provided as a machine-readable medium for storing the machine-executable instructions. The machine-readable medium may include, but is not limited to, floppy diskettes, optical disks, CD-ROMs, and magneto-optical disks, ROMs, RAMs, EPROMs, EEPROMs, magnetic or optical cards, propagation media or other type of media/machine-readable medium suitable for storing electronic instructions. For example, the present invention may be downloaded as a computer program which may be transferred from a remote computer (e.g., a server) to a requesting computer (e.g., a client) by way of data signals embodied in a carrier wave or other propagation medium via a communication link (e.g., a modem or network connection).

Throughout the foregoing description, for the purposes of explanation, numerous specific details were set forth in order to provide a thorough understanding of the invention. It will be apparent, however, to one skilled in

the art that the invention may be practiced without some of these specific details.

For example, while the system described above employs a single portal server 110, alternative embodiments of the invention may include numerous different servers (e.g., database servers, web servers, etc), and/or mirrored servers

5 distributed across a network. Moreover, while the embodiments described above focus on a portal device which executes interpreted code (e.g., Java bytecodes), the principles of the invention may also be implemented on devices which execute non-interpreted code. Accordingly, the scope and spirit of the invention should be judged in terms of the claims which follow.

10